

# OMNII XT15



## ADAPTABILITY GIVES YOU MORE

The Omnii™ XT15 is uniquely adaptive by design — combining extreme versatility with open innovation to deliver the flexibility you require to adapt as your business needs change. As the next evolution of the Omnii platform, the Omnii XT15 takes the best features of the Omnii XT10 and adds new functionality to create a device that gives mobile workers the greatest access to business applications — anytime, anywhere. With its certified IP67 and IP65 rating, the Omnii XT15 delivers reliable performance and unparalleled adaptability for the most demanding of environments and applications. Find out why Omnii XT15 is the ultimate supply chain handheld solution.



### Technology made tough

The Omnii XT15 comes with the option of Windows® CE 6.0 or Windows® Embedded Handheld 6.5 operating systems, both of which integrate seamlessly to automate key processes and boost productivity in real-time. Plus, it is certified IP67 and IP65 so it will work wherever you take it.

### Field-upgradeable adaptability

Omnii XT15 is always fit for purpose, so you can configure it the way you want and later bolt on what you need. This allows for future-proof flexibility as hardware can be reconfigured — and not replaced — saving your business up to 30% on lifetime total cost of ownership.

### Optimized ergonomics

Ergonomics are crucial to ensuring mobile workers are efficient and effective on their jobs. The Omnii XT15 features a balanced construction that is perfectly weighted for comfort, practicality and Natural Task Support. Furthermore, Omnii XT15 is equipped with Kiosk Mode software and transfective touch screens that enable a friendly user interface.

### Rugged design for superior reliability and TCO

With a dual IP65 and IP67 sealing rating, workers can spill water on or even drop the device in a puddle of water — or work out in the pouring rain. And even a 6.5 ft./2 m drop to concrete won't impact operation.

### Flexible wireless connectivity options

Only Zebra allows you to choose between cellular, Wi-Fi or Narrowband wireless connectivity, bringing you the most wireless options in one device. Support for 802.11a/b/g/n Wi-Fi provides compatibility with virtually any wireless LAN and plenty of bandwidth to support the modern graphical user interfaces of today's demanding applications. Narrowband support provides robust, affordable and secure wireless connectivity for simple data transactions in expansive outdoor areas such as seaports, rail yards, airports and expansive outdoor yards in manufacturing plants. And support for GSM/GPRS/EDGE and HSPA+ provides fast and reliable connectivity for field workers all around the world.

### Real-world practicality

Zebra understands how to make mobile workers more productive in the harshest of environments and we have designed all elements of the Omnii XT15 to reflect that expertise. Built with the Texas Instruments® OMAP3 microprocessor and a designed Custom ASIC architecture, Omnii XT15 delivers industry-leading performance and efficiency with an extended battery life of up to 20 hours. The 3.7 in. VGA color display allows for improved worker visibility and the 95db keypad beeper with vibration feedback is perfect for loud industrial environments.

**THE ULTIMATE HANDHELD FOR SUPPLY CHAIN LOGISTICS**

VISIT [WWW.ZEBRA.COM/OMNIIXT15](http://WWW.ZEBRA.COM/OMNIIXT15) OR ACCESS OUR CONTACT DIRECTORY AT [WWW.ZEBRA.COM/CONTACT](http://WWW.ZEBRA.COM/CONTACT)

# OMNII XT15 Specs

## PHYSICAL CHARACTERISTICS

<b>Dimensions</b>	8.86 in. L x 3.86 in. W x 1.73 in. D (at display); 1.22 in. D (at grip area); 225 mm L x 98 mm W x 44 mm D (at display); 31 mm D (at grip area)
<b>Weight</b>	1.34 lbs./610 g (basic unit with battery)
<b>Keyboard Options</b>	59-key full alpha numeric; 55-key Alpha Numeric; 66-key QWERTY Numeric 36-key Numeric; 36-key Numeric Alpha Modified; 36-key Numeric; Ultra-white backlight
<b>Power</b>	PowerPrecision Lithium ion battery 5000 mAh
<b>Display</b>	3.7" VGA (640 x 480) Transflective Color/Touch Display; 2 Touchscreen options: High Visibility option, Extreme Duty option
<b>Audio</b>	Integrated microphone and speaker; high volume 95dBA beeper; optional push-to-talk speaker; vibration feedback
<b>Camera (optional)</b>	3 Mega pixel, autofocus, 4X digital zoom, Dual LED flash, Video capable
<b>GPS (optional)</b>	SIRF III GPS Receiver

## PERFORMANCE CHARACTERISTICS

<b>CPU</b>	TI OMAP 3, 800 MHz
<b>Operating System</b>	Windows® CE 6.0; Windows® Embedded Handheld 6.5
<b>Memory</b>	512 MB RAM and 1GB Flash
<b>Bundled Applications</b>	Windows CE 6.0: Internet Explorer Embedded; Microsoft Wordpad Windows Embedded Handheld 6.5: Windows® Office Mobile 2010 (includes Word, Excel, PowerPoint, OneNote and SharePoint); Internet Explorer Mobile; Windows Office Outlook Mobile; Windows Media Player Mobile
<b>Terminal Emulation</b>	TekTerm; Wavelink
<b>Additional Software</b>	NetMotion Mobility XE VPN; Mobile Control Center (MCC); Kiosk Mode; Total Recall/TweakIt/Dr. Debug

## BAR CODE SCANNER OPTIONS

SE955 1-D Laser; SE965 1-D Laser, SE1224HP 1-D Laser, SE1524ER Extended Range Laser; SE4500 1-D/2-D Standard Range Imager; SE4600 1-D/2-D Extended Range Imager

## RFID MODULE OPTIONS

<b>HF Module*</b>	Frequency: 13.56 MHz; Protocols supported: ISO14443 type A, B and C, ISO 15693; NFC "Reader to Tag" Mode; full Mifare support; Data encryption: 2 SAM slots; ID1 SAM format; Class A, B and C
-------------------	---

## ACCESSORIES

Switchable Keyboard, Integrated 1-D, 2-D and AutoRange Scanners, Desktop Docking Station, 6-Slot Spare Battery Charger, Vehicle Cradle, Carry Accessories. For a complete list of accessories, visit: [www.zebra.com/omniixt15](http://www.zebra.com/omniixt15).

## USER ENVIRONMENT

<b>Operating Temp.</b>	-20°C to +50°C / -4°F to +122°F
<b>Storage Temp.</b>	-40°C to +60°C / -40°F to +140°F
<b>Humidity</b>	5% to 95% non-condensing
<b>Sealing</b>	IP67, IP65, IEC 60529
<b>Drop Specification</b>	Multiple 6.5 ft./2 m drops to polished concrete
<b>Integrated Sensors</b>	Motion (accelerometer); digital compass
<b>ESD</b>	+/- 8kV contact, +/- 15kV air discharge

## WIRELESS DATA COMMUNICATIONS

<b>WLAN</b>	IEEE 802.11a/b/g/n, CCX v4, 802.1X, WPA / WPA2-Enterprise & Shared Key, FAST-MSCHAPv2; LEAP; PEAPv0-MSCHAPv2; PEAPv1-GTC; TLS, 64/128 WEP, AESCCMP, TKIP
<b>Narrow-band* (optional)</b>	UHF bands: 403 – 470 MHz Channel Spacing: 12.5 – 25 kHz RF power: 500 - 1,000mW; Transmission speed: 4.8/9.6 kbps @ 12.5 kHz, 9.6/19.2 kbps @ 25 kHz
<b>WWAN (optional)</b>	2.5G GSM/GPRS/EDGE radio, Quad-Band GSM: 850, 900, 1800, 1900 MHz; UMTS 3.8G HSPA+ radio, Five Band UMTS: 800/850, 900, 1900, 2100 MHz, Quad-Band GSM: 850, 900, 1800, 1900 MHz
<b>WPAN</b>	Bluetooth® V2.0 + EDR

## REGULATORY

Worldwide Safety, EMC, RF, Laser approvals; CE Mark; E Mark (vehicle cradles); RoHS compliant; WEEE compliant; REACH compliant

## WARRANTY

Subject to the terms of Zebra's hardware warranty statement, the Omnii XT15 is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, go to: [www.zebra.com/warranty](http://www.zebra.com/warranty)

## SERVICES AND SUPPORT

**Service from the Start Primary:** A unique service that covers normal wear and tear as well as accidental damage to internal and external components. Includes a collection option with pre-paid ground freight on return shipments.

\* HF Module cannot be combined with the following: Omnii XT15f freezer model, Omnii XT15NI model, Long range imager SE4600, Long range laser SE1524ER, Pistol Grip

\* Narrowband is only available on CE models. Narrowband cannot be combined with the following: Omnii XT15F Freezer Model, WWAN radio, Long Range Imager SE4600, Long Range Laser SE1524ER, Camera Speaker, Motion sensor (accelerometer)

## Ideal For These Applications:

### Industries

- Warehousing
- Manufacturing
- Distribution and Logistics
- Utilities
- Transportation and Logistics



Corporate and International Headquarters | [Zebra.com/contact](http://Zebra.com/contact)

# DATOS DE CONTACTO REGIONAL Y REDES SOCIALES



(507) 270-4444 Panamá  
(502) 2326-8383 Guatemala  
(503) 2526-9206 El Salvador  
(504) 2566-0426 Honduras  
(505) 2266-2050 Nicaragua  
(506) 4000-0482 Costa Rica  
5528654081 México

[www.grupo-megabyte.net](http://www.grupo-megabyte.net)  
[info@grupo-megabyte.net](mailto:info@grupo-megabyte.net)

Redes Sociales:



[GrupoMegabyteCA](#)



[GrupoMegabyte](#)



[GrupoMegabyte01](#)



[GrupoMegabyteCA](#)



[GrupoMegabyte](#)